

xTablet Flex 10A with Android

The lightweight, rugged, entry level tablet with Android

lobile**Demano**

The proven rugged Flex 10A is now available with next level Android 9.0 O/S performance, powered by the MT8163 Quad-Core Processor. Its GMS certification offers the highest level of security and (OTA) management features, meeting Google's stringent performance standards. Designed with clever built-in features that include a briefcase handle and back hand strap for easy portability along with our patented snap mount system for unlimited mounting solutions in any environment. Protected by MobileDemand's extremely durable xCase, scratch-proof screen protector and coupled with ample storage and power make it the perfect solution for light to medium-duty mobile applications and an ideal entry-level rugged tablet for construction, agriculture, distribution, and retail industries.

Highlights

Rugged, lightweight form factor
Quick release mounting
Android 9.0 O/S
SOTI Certified
Industry-leading value pricing
Keyboard option ready
Optional integrated Magstripe Reader
10.1″ display



features

Accessories

Snap mount Briefcase handle Back hand strap Keyboard Integrated Magstripe Reader Stylus, tether and holder 2-point and 4-point shoulder straps

Warranty

The xTablet Flex10A with Android comes with a 1-year warranty that covers hardware failure when the tablet has been used as designed. In addition, MobileDemand offers extended coverage with <u>xProtect</u>.

android



©2020 MobileDemand, LC MobileDemand and xTablet Flex 10A are trademarks. VERSION June 25, 2020

Specifications		
DIMENSIONS	With case (excluding bumpers): 10.5" W x 7.2" H x .7" D (267mm W x 182mm H x 18.5mm D)	
WEIGHT	2.07 lb. (.94 kg) - base config	
DISPLAY	10.1" Capacitive 1280 (W) x 800 (H) IPS 250 NITS	
CPU	MT8163 64-bit CPU, Quad-Core Cortex-A53, 1.3GHz	
MEMORY	3GB PCDDR3	
STORAGE	128GB	
O/S	Android 9.0 Pie	
EMM CERTIFICATION	SOTI	

SECURE PAYMENT

RUGGEDIZED	MIL-STD 810G (5ft passed)
Screen Protector	Oleophobic, scratch-resistant glass
Operating Temp	14° F to +113° F (-10° C to 45° C)
Storage Temp	-4° F to +140° F (-20° C to 60° C)
Operating Humidit	y 5% - 95% non-condensing
CAMERA	Front - 2MP Rear - 5MP
I/O PORTS	Micro USB OTG USB 2.0 Mini HDMI Headphone DC Barrel Jack
AUDIO	$3W \times 1 @ 4\Omega$, 2 integrated speakers
BUTTONS	Power; Volume +/-
SENSORS	Accelerometer
BATTERY SYSTEM	Lithium-ion polymer battery 14.8Wh, 4000mAh, 3.7V, up to 4-6 hours ¹ of battery life
WIRELESS/NETWO	ORK
WLAN	WIFI 802.11 a/b/g/n
Bluetooth	4.0
AGENCY APPR	FCC-CE-IC



¹Battery life varies significantly depending on settings, app usage, and other factors

Powered by